

QuickScan® QS6000 Plus

Handheld Scanner

Data Sheet



Ideal for:

- Retail Applications
- Health Care
- Inventory
- Office Automation
- Light Industrial

Features:

- Great depth-of-field
- AutoSense® stand for hands-free operation
- Optional EAS antenna for simultaneous scanning and security tag deactivation
- Universal wedge for additional keyboard emulation, bar code symbologies, and data editing
- Sunrise 2005 Compliant
- RSS decoding available on select models

Mechanical

Dimensions

Height: 6.5" / 16.5cm

Width: 2.8" / 7cm

Length: 4.2" / 10.7cm

Weight: 6.0 oz. / 184 g (scanner)

Environmental

Temperature Rating

Operating: 32° to 122° F / 0° to 50°C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Shock (at 23° C): Withstands multiple 5' / 1.5m drops onto concrete (100+ drops to countertop)

Water & Dust: Resistant, IEC529 rating IP53DW

Vibration: MIL-STD-810E

Optical

Light Source: 650nm Visible Laser Diode (VLD)

Scan Rate: 42 scans/sec (nominal)

Scan System: Electromagnetic dithering mirror

Resolution: 5 mils (13mm)

Print Contrast: 30% minimum

Pitch: ±65°

Skew: ±55°

Scan angle: 46°

Ambient Light Immunity

Artificial Light: 1,200 foot candles / 12,900 Lux

Sunlight: 8,000 foot candles / 81,600 Lux

Depth of Field: Refer to Chart below

DEPTH OF FIELD* Range Comparisons	
LABEL DENSITY	RANGE
5 mils	10 — 30" / 2.5 — 76 cm
7.5 mils	0.5 — 6.0" / 13 — 152 cm
10 mils	0 — 9" / 0 — 22.9 cm
13 mils	0 — 13" / 0 — 33 cm
20 mils	Up to 20" / Up to 50.8 cm

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Electrical

Operating Voltage:

Undecoded: 4.2 V to 14 VDC

Decoded: 4.5 V to 14 VDC

Operating Current - nominal

Undecoded: 70 mA to 5 VDC

Decoded: 120 mA to 5 VDC

Idle Current - nominal

Undecoded: 10 µA to 5 VDC

Decoded: 23 mA to 5 VDC

Decoded lowest power mode: 14 mA to 5 VDC

Communications

- RS-232
- Standard Keyboard Wedge
- Universal Keyboard Wedge
- IBM 46XX
- USB
- Wand Emulations
- OCIA
- Undecoded

Decoding Capability

- UPC A, E / EAN 8, 13 / JAN 8, 13 (Codes Add-ons P2/P5)
- Code 128 / EAN 128
- Pharmacoce 39
- Interleaved 2 of 5
- Code 39
- RSS on selected models
- Codabar
- Code 93
- Standard 2 of 5
- IATA
- MSI/Plessey

Safety & Regulatory

Electrical: Complies to Gost R; TÜV; UL; cUL

Emissions: Complies to FCC-A; EN 55022-B; BCIQ CNS 13438; AS/NZS 3548; VCCI-B

Laser Classification: CDRH Class IIa;

(Caution: Laser Radiation - do not stare into beam); IEC 60825 Class 1 & 2



Available Mounting Options



P/N: 7-0204
AutoSense®

P/N: 7-0470
AutoSense®
(w/o base)

P/N: 5-0788
Universal Holster

P/N: 7-0393
Mountable
Tabletop

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140



© 2005 PSC Inc. All rights reserved. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. PSC, QuickScan, and the PSC logo are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.

R45-2010-US M 0505

